

Rolling Shutters

(Non-Extruded)

2000 Series – Non-Code Approved.

Our “**2000 Series**” 55mm **Non-Extruded Aluminum** shutter and uses a lightweight aluminum outside with a **Foam-Filled** inside slat profile. It is designed primarily for the greatest of **insulation and sound proofing** qualities for any type opening and size opening.

While **Non-Code approved**, it is good for storm protection, security, privacy and shade on wider and taller openings in most areas.

You can use the 55mm formula found on the “**Box Size and Capacity Chart**” page to determine the finished shutter size and square footage. This will help you pick the method of operation needed. Any of the operation methods are usable with the “**2000**” series shutter considering you don’t exceed the maximum weight limitations.

The **pull strap system** can be used up to 35 square feet of the finished sized shutter.

It can be **manually cranked** up to 90 square feet of finished size shutter with the use of an assist spring. Any shutter larger than 90 sq ft will require a **motorized system**. A motor can be added as an option with a shutter of any size.

Storm bars and header are **optional** and up to the **discretion of the consumer** to add to the wider spanned openings. They will help reduce the amount of flexing during high wind pressures.

The “**2000 Series**” shutter system is great for exterior general storm protection and security on, windows, open patios, lanais, residential homes, apartments, businesses store fronts, over garage doors, carports, trash areas, gazebos, cabanas and entertainment areas. They can be used **inside** as a safe room retreat, partition between rooms, pharmacy counters, reception areas, Laundromats, and room dividers as well. There are unlimited possibilities and options for this shutter depending on your needs.